

# VELUX NIGHT LIGHT KIT

Turn your VELUX Sun Tunnel into a light source at night!

## Installation Instructions

1. Pre-drill a 9/16 hole through the lower stainless steel ring so that the conduit can be passed through. The hole should be centered 2 5/8 " from the bottom of stainless ring. The hole should be drilled so the conduit has plenty of clearance and does not hit ceiling joists.
2. Remove the junction box adapter from the other end of the conduit. Pass the loose end of the conduit through the hole, from the inside, until the base plate of the night light is flush against the stainless ring. Install the two - # 8 x 3/4 " self tapping screws (provided) through the pre-drilled holes in the base plate, through the lower stainless ring and into the plastic ceiling frame.
3. Re-attach the junction box adapter onto the loose end of the conduit and secure the 2-slot head screws to lock the adaptor to the conduit. The loose end is now ready to be screwed into the standard electrical junction box (not provided) and fastened to a ceiling joist near the Sun Tunnel. The junction box will need to be supplied with a switched 120 V power supply.

4. Install a fluorescent lamp (not provided) into light socket. We recommend either a 22 watt, equivalent to 75 watt IL\* or a 43 Watt equivalent to a 150 watt IL\* and far less energy to run.

\*Incandescent lamp

*Not intended to replace the primary electric light source in a room.*

Installation should be performed by a Licensed Electrical Contractor to conform with your local code requirements.

Manufactured with UL approved socket and flexible conduit.

For other questions please contact VELUX customer service at 1-800-888-3589